

POWER TOOLS & ABRASIVES

MAKITA POWER TOOLS เครื่องมือไฟฟ้า “มาคิต้า”



มาคิต้า

HR1840

Rotary Hammer

18 mm (11/16") 1.4 J
Rotary Hammer, SDS-PLUS Bits



Continuous rating Input	470W
Impact Energy	EPTA-Procedure 05/2009: 1.4 J
Capacity	Concrete: 18 mm (11/16") Steel: 13 mm (1/2") Wood: 24 mm (15/16") Masonry: 18 mm (11/16")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Blows Per Minute (BPM)	0 - 4,800
No Load Speed (RPM)	0 - 2,100
Dimensions (L x W x H)	285 x 75 x 208 mm (11-1/4 x 3 x 8-3/16")
Net weight	2 - 2.4 kg (4.3 - 5.3 lbs.)
Power supply cord	2.5 m (8.2 ft)

HR2230

Rotary Hammer

22 mm (7/8") 2.2 J
Rotary Hammer, SDS-PLUS Bits



Continuous rating Input	710W
Impact Energy	EPTA-Procedure 05/2009: 2.2 J
Capacity	Concrete (w/ TCT Bit): 22 mm (7/8") Concrete (w/ Diamond Core Bit): 65 mm (2-9/16") Steel: 13 mm (1/2") Wood: 32 mm (1-1/4") Wood (Self-Feed Bit): 32 mm (1-1/4") Masonry: 22 mm (7/8")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Blows Per Minute (BPM)	0 - 4,050
No Load Speed (RPM)	0 - 1,050
Dimensions (L x W x H)	357 x 84 x 214 mm (14 x 3-5/16 x 8-3/8")
Net weight	2.6 - 3.1 kg (5.8 - 6.8 lbs.)
Power supply cord	2.5 m (8.2 ft)

HR2470FT

Combination Hammer

24 mm (15/16"), Adapted for SDS-PLUS bits



Continuous rating input	780W
Impact Energy	EPTA-Procedure 05/2009: 2.4 J
Capacity	Concrete: 24 mm (15/16") Steel: 13 mm (1/2") Wood: 32 mm (1-1/4")
Blows Per Minute (BPM)	0 - 4,500
No Load Speed (RPM)	0 - 1,100
Sound Pressure Level	90 dB(A)
Sound Power Level	101 dB(A)
Vibration Level	Hammer Drilling into Concrete: 15.5 m/s ² Drilling into Metal: 4.5 m/s ²
Dimensions (L x W x H)	394x84x214 mm (15-1/2"x3-5/16"x8-3/8")
Net weight	3.0 - 3.3 kg (6.7 - 7.3 lbs.)
Power supply cord	4.0 m (13.1 ft)

HR2470F

Combination Hammer

24 mm (15/16"), Adapted for SDS-PLUS bits



Continuous rating input	780W
Impact Energy	EPTA-Procedure 05/2009: 2.4 J
Capacity	Concrete: 24 mm (15/16") Steel: 13 mm (1/2") Wood: 32 mm (1-1/4")
Blows Per Minute (BPM)	0 - 4,500
No Load Speed (RPM)	0 - 1,100
Sound Pressure Level	90 dB(A)
Sound Power Level	101 dB(A)
Vibration Level	Hammer Drilling into Concrete: 15.5 m/s ² Drilling into Metal: 4.5 m/s ²
Dimensions (L x W x H)	370x84x214 mm (14-1/2"x3-5/16"x8-3/8")
Net weight	2.9 - 3.3 kg (6.4 - 7.3 lbs.)
Power supply cord	4.0 m (13.1 ft)

HR2475

Combination Hammer

24 mm (15/16") Adapted for SDS-PLUS bits



Continuous rating input	780W
Impact Energy	EPTA-Procedure 05/2009: 2.3 J
Capacity	Concrete: 24 mm (15/16") Steel: 13 mm (1/2") Wood: 32 mm (1-1/4")
Blows Per Minute (BPM)	0 - 4,500
No Load Speed (RPM)	0 - 1,100
Sound Pressure Level	89 dB(A)
Sound Power Level	100 dB(A)
Vibration Level	Hammer Drilling into Concrete: 15.5 m/s ²
Dimensions (L x W x H)	429x84x158 mm (16-7/8"x3-5/16"x6-1/4")
Net weight	3.0 - 3.4 kg (6.6 - 7.6 lbs.)
Power supply cord	4.0 m (13.1 ft)

HR2631F

Combination Hammer

26 mm (1") 2.4 J AVT Combination Hammer, SDS-PLUS Bits, LED Light



Continuous rating Input	800W
Impact Energy	EPTA-Procedure 05/2009: 2.4 J
Capacity	Concrete: 26 mm (1") Steel: 13 mm (1/2") Wood: 32 mm (1-1/4") Wood (Self-Feed Bit): 32 mm (1-1/4") Masonry: 26 mm (1")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Blows Per Minute (BPM)	0 - 4,600
No Load Speed (RPM)	0 - 1,200
Dimensions (L x W x H)	361 x 77 x 209 mm (14-1/4 x 3 x 8-1/4")
Net weight	2.9 - 3.4 kg (6.4 - 7.4 lbs.)
Power supply cord	2.5 m (8.2 ft)

HR2631FT

Combination Hammer

26 mm (1") 2.4 J AVT Combination Hammer, SDS-PLUS Bits, Quick Change Chuck, LED Light




Continuous rating Input	800W
Impact Energy	EPTA-Procedure 05/2009: 2.4 J
Capacity	Concrete: 26 mm (1") Steel: 13 mm (1/2") Wood: 32 mm (1-1/4") Wood (Self-Feed Bit): 32 mm (1-1/4") Masonry: 26 mm (1")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Blows Per Minute (BPM)	0 - 4,600
No Load Speed (RPM)	0 - 1,200
Dimensions (L x W x H)	385 x 77 x 209 mm (15-1/8 x 3 x 8-1/4")
Net weight	3.1 - 3.6 kg (6.8 - 7.9 lbs.)
Power supply cord	2.5 m (8.2 ft)

HR2653

Combination Hammer with Self Dust Collection

26 mm (1") 2.2 J AVT Combination Hammer with HEPA Self Dust Collection, SDS-PLUS Bits



Continuous rating Input	800W
Impact Energy	EPTA-Procedure 05/2009: 2.2 J
Capacity	Concrete: 26 mm (1") Steel: 13 mm (1/2") Wood: 32 mm (1-1/4") Wood (Self-Feed Bit): 32 mm (1-1/4") Masonry: 26 mm (1")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Blows Per Minute (BPM)	0 - 4,600
No Load Speed (RPM)	0 - 1,200
Dimensions (L x W x H)	604 x 89 x 260 mm (23-3/4 x 3-1/2 x 10-1/4")
Net weight	3.1 - 4.3 kg (6.9 - 9.6 lbs.)
Power supply cord	2.5 m (8.2 ft)

HR2661

Combination Hammer with Self Dust Collection

26 mm (1"), Adapted for SDS-PLUS bits



Continuous rating input	800W
Impact Energy	EPTA-Procedure 05/2009: 2.2 J
Capacity	Concrete: 26 mm (1") Core Bit: 68 mm (2-11/16") Steel: 13 mm (1/2") Wood: 32 mm (1-1/4")
Blows Per Minute (BPM)	0 - 4,500
No Load Speed (RPM)	0 - 1,100
Sound Pressure Level	90 dB(A)
Sound Power Level	101 dB(A)
Vibration Level	Hammer Drilling Into Concrete: 9.5 m/s ²
Dimensions (L x W x H)	666x89x228 mm (26-1/4"x3-1/2"x9")
Net weight	3.3 - 4.4 kg (7.3 - 9.7 lbs.)
Power supply cord	2.5 m (8.2 ft)

HR2810

Combination Hammer

28 mm (1-1/8") 2.8 J Combination Hammer, SDS-PLUS Bits



Continuous rating Input	800W
Impact Energy	EPTA-Procedure 05/2009: 2.8 J
Capacity	Concrete (w/ TCT Bit): 28 mm (1-1/8") Steel: 13 mm (1/2") Wood: 32 mm (1-1/4") Wood (Self-Feed Bit): 32 mm (1-1/4")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Blows Per Minute (BPM)	0 - 4,500
No Load Speed (RPM)	0 - 1,100
Dimensions (L x W x H)	314 x 89 x 225 mm (12-3/8 x 3-1/2 x 8-7/8")
Net weight	3.4 - 3.8 kg (7.5 - 8.5 lbs.)
Power supply cord	2.5 m (8.2 ft)

HR2810T

Combination Hammer

28 mm (1-1/8") 2.9 J Combination Hammer, SDS-PLUS Bits, Quick Change



Continuous rating Input	800W
Impact Energy	EPTA-Procedure 05/2009: 2.9 J
Capacity	Concrete (w/ TCT Bit): 28 mm (1-1/8") Steel: 13 mm (1/2") Wood: 32 mm (1-1/4") Wood (Self-Feed Bit): 32 mm (1-1/4") Masonry: 28 mm (1-1/8")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Blows Per Minute (BPM)	0 - 4,500
No Load Speed (RPM)	0 - 1,100
Dimensions (L x W x H)	339 x 89 x 225 mm (13-3/8 x 3-1/2 x 8-7/8")
Net weight	3.5 - 3.8 kg (7.8 - 8.4 lbs.)
Power supply cord	2.5 m (8.2 ft)

HR2811F

Combination Hammer

28 mm (1-1/8") 2.8 J Combination Hammer, SDS-PLUS Bits, LED Light



Continuous rating Input	800W
Impact Energy	EPTA-Procedure 05/2009: 2.8 J
Capacity	Concrete (w/ TCT Bit): 28 mm (1-1/8") Steel: 13 mm (1/2") Wood: 32 mm (1-1/4") Wood (Self-Feed Bit): 32 mm (1-1/4") Masonry: 28 mm (1-1/8")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Blows Per Minute (BPM)	0 - 4,500
No Load Speed (RPM)	0 - 1,100
Dimensions (L x W x H)	320 x 89 x 225 mm (12-5/8 x 3-1/2 x 8-7/8")
Net weight	3.5 - 3.9 kg (7.7 - 8.7 lbs.)
Power supply cord	2.5 m (8.2 ft)