



NEW
UM-ZL28



NEW
UM-ZF100



- Anti vibration rubber isolator for easy removal and maintenance of head/board
- UM-ZF100 is for external vibration, ideal for construction of walls, pillars, etc.

UM Specifications

model	vib.head dia. [D] x shaft length [A] (mm)	vib.board size (mm)	amplitude (mm)	vibration Hz (V.P.M.)	power (W) (single phase)	weight(kg)
UM-Z28	28 x 785	—	1.4	200-258 (12,000-15,500)	280	5.3
UM-ZF100	—	100(W) x 78(T)	—	166-200 (10,000-12,000)		5.2

GS Concrete Vibrator

Coupling type



- Mikasa original
- Pin type
- Two claws type



Hose (4m·6m)

GS Specifications

model	vib.head dia. x length (mm)	flexible shaft dia. (mm)	rubber casting dia. (mm)	rubber hose (m)	amplitude (mm)	vibration Hz (V.P.M.)	shaft set weight 4m / 6m (kg)
GS-28	28 x 477	10	30	4 or 6	1.4	150-208 (9,000-12,500)	10.6 / 14.7
GS-32	32 x 520				1.8		11.2 / 15.1
GS-38	38 x 480				2.0		11.9 / 15.7
GS-45	45 x 494				2.4		13.3 / 17.4
GS-60	60 x 479	13	32	6	2.4		22.3