

POWER TOOLS & ABRASIVES

MAKITA POWER TOOLS เครื่องมือไฟฟ้า “มาคิต้า”

12V max
LITHIUM-ION

CXT

Makita

มาคิต้า

DF333D Cordless Driver Drill 12V max

12Vmax CXT Li-Ion Cordless
10 mm (3/8") 28 N-m (250 in.lbs.)
Driver Drill



Capacity	Steel: 10 mm (3/8") Wood (Self-Feed Bit): 42 mm (1-5/8")
Chuck Capacity	Wood: 21 mm (13/16")
No Load Speed (RPM)	0.8 - 10 mm (1/32 - 3/8")
Max Fastening Torque	High / Low: 0 - 1,700 / 0 - 450
Max Lock Torque	Hard / Soft: 30 / 14 N-m (270 / 130 in.lbs.)
Dimensions (L x W x H)	w/ BL1016/BL1021B : 179 x 66 x 212 mm (7 x 2-5/8 x 8-3/8")
Net weight	1.1 - 1.2 kg (2.4 - 2.7 lbs.)

DF033D Cordless Driver Drill 12V max

12Vmax CXT Li-Ion Cordless
6.35 mm (1/4") Hex 28 N-m (250 in.lbs.)
Driver Drill



Capacity	Steel: 10 mm (3/8") Wood (Self-Feed Bit): 42 mm (1-5/8")
Chuck Capacity	Wood: 21 mm (13/16")
No Load Speed (RPM)	0.8 - 10 mm (1/32 - 3/8")
Max Fastening Torque	High / Low: 0 - 1,700 / 0 - 450
Max Lock Torque	Hard / Soft: 30 / 14 N-m (270 / 130 in.lbs.)
Dimensions (L x W x H)	w/ BL1016/BL1021B : 149 x 66 x 212 mm (5-7/8 x 2-5/8 x 8-3/8")
Net weight	0.9 - 1.1 kg (2.1 - 2.4 lbs.)

DF332D Cordless Driver Drill 12V max

12Vmax CXT BL Brushless Cordless
10 mm (3/8") 32 N-m (280 in.lbs.)
Driver Drill



Capacity	Steel: 10 mm (3/8") Wood (Self-Feed Bit): 56 mm (2-3/16")
Chuck Capacity	Wood: 28 mm (1-1/8")
No Load Speed (RPM)	0.8 - 10 mm (1/32 - 3/8")
Max Fastening Torque	High / Low: 0 - 1,500 / 0 - 450
Max Lock Torque	Hard / Soft: 35 / 21 N-m (310 / 190 in.lbs.)
Dimensions (L x W x H)	154 x 66 x 217 mm (6-1/16 x 2-5/8 x 8-1/2")
Net weight	1 - 1.2 kg (2.3 - 2.6 lbs.)

DF032D Cordless Driver Drill 12V max

12Vmax CXT BL Brushless Cordless
6.35 mm (1/4") Hex 32 N-m (280 in.lbs.)
Driver Drill



Capacity	Steel: 10 mm (3/8") Wood (Self-Feed Bit): 56 mm (2-3/16") Wood: 28 mm (1-1/8")
Chuck Capacity	6.35 mm (1/4")
No Load Speed (RPM)	High / Low: 0 - 1,500 / 0 - 450
Max Fastening Torque	Hard / Soft: 35 / 21 N-m (310 / 190 in.lbs.)
Max Lock Torque	32 N-m (280 in.lbs.)
Dimensions (L x W x H)	124 x 66 x 217 mm (4-7/8 x 2-5/8 x 8-1/2")
Net weight	0.88 - 1 kg (1.9 - 2.3 lbs.)

HP333D Cordless Hammer Driver Drill 12V max

12Vmax CXT Li-Ion Cordless
10 mm (3/8") 28 N-m (250 in.lbs.)
Hammer Driver Drill



Capacity	Steel / Wood / Masonry : 10 / 21 / 8 mm (3/8 / 13/16 / 5/16") Wood (Self-Feed Bit): 42 mm (1-5/8")
Chuck Capacity	0.8 - 10 mm (1/32 - 3/8")
Impacts Per Minute (IPM)	High / Low: 0 - 25,500 / 0 - 6,750
No Load Speed (RPM)	High / Low: 0 - 1,700 / 0 - 450
Max Fastening Torque	Hard / Soft: 30 / 14 N-m (270 / 130 in.lbs.)
Max Lock Torque	28 N-m (250 in.lbs.)
Dimensions (L x W x H)	w/ BL1016/BL1021B : 193 x 66 x 212 mm (7-5/8 x 2-5/8 x 8-3/8")
Net weight	1.1 - 1.3 kg (2.4 - 2.9 lbs.)

HP332D Cordless Hammer Driver Drill 12V max

12V max CXT BL Brushless Cordless
10 mm (3/8") 32 N-m (280 in.lbs.)
Hammer Driver Drill



Capacity	Steel / Wood / Masonry : 10 / 28 / 8 mm (3/8 / 1-1/8 / 5/16") Wood (Self-Feed Bit): 56 mm (2-3/16")
Chuck Capacity	0.8 - 10 mm (1/32 - 3/8")
Impacts Per Minute (IPM)	High / Low: 0 - 22,500 / 0 - 6,750
No Load Speed (RPM)	High / Low: 0 - 1,500 / 0 - 450
Max Fastening Torque	Hard / Soft: 35 / 21 N-m (310 / 190 in.lbs.)
Max Lock Torque	32 N-m (280 in.lbs.)
Dimensions (L x W x H)	168 x 66 x 217 mm (6-5/8 x 2-5/8 x 8-1/2")
Net weight	1.1 - 1.3 kg (2.4 - 2.8 lbs.)

DA333D Cordless Angle Drill 12V max

12V max CXT Li-Ion Cordless
10 mm (3/8") Angle Drill,
Keyless Chuck



Capacity	Steel: 10 mm (3/8") Wood: 12 mm (1/2") Wood (Self-Feed Bit): 24 mm (15/16")
Chuck Capacity	0.8 - 10 mm (1/32 - 3/8")
No Load Speed (RPM)	0 - 1,100
Head Height	84 mm (3-5/16")
Center Height	23.5 mm (15/16")
Dimensions (L x W x H)	w/ BL1016/BL1021B: 313 x 68 x 95 mm (12-3/8 x 2-11/16 x 3-3/4")
Net weight	1.2 - 1.4 kg (2.7 - 3 lbs.)

TD111D Cordless Impact Driver 12V max

12V max CXT BL Brushless Cordless
A-Mode (Assist Mode)
135 N-m (1,200 in.lbs.)
Impact Driver



Capacity	Machine Screw: M4 - M8 mm (5/32 - 5/16") Standard Bolt: M5 - M14 (3/16 - 9/16") High Strength Bolt: M5 - M12 (3/16 - 1/2") Coarse thread (in length) : 22 - 90 mm (7/8 - 3-1/2")
Hex Shank	6.35 mm (1/4")
No Load Speed (RPM)	0 - 3,000 / 0 - 1,300
Impacts Per Minute (IPM)	0 - 3,900 / 0 - 1,600
Max Fastening Torque	135 N-m (1,200 in.lbs.)
Dimensions (L x W x H)	135 x 66 x 210 mm (5-5/16 x 2-5/8 x 8-1/4")
Net weight	0.97 - 1.1 kg (2.1 - 2.5 lbs.)

TD110D Cordless Impact Driver 12V max

12V max CXT Li-Ion Cordless
110 N-m (970 in.lbs.)
Impact Driver



Capacity	Machine Screw: M4 - M8 mm (5/32 - 5/16") Standard Bolt: M5 - M12 (3/16 - 1/2") High Strength Bolt: M5 - M10 (3/16 - 3/8") Coarse thread (in length) : 22 - 90 mm (7/8 - 3-1/2")
Hex Shank	6.35 mm (1/4")
No Load Speed (RPM)	0 - 2,600
Impacts Per Minute (IPM)	0 - 3,500
Max Fastening Torque	110 N-m (970 in.lbs.)
Dimensions (L x W x H)	153 x 66 x 204 mm (6 x 2-5/8 x 8-1/8")
Net weight	1 - 1.2 kg (2.3 - 2.6 lbs.)

TL064D Cordless Angle Impact Driver 12V max

12V max CXT Li-Ion Cordless
60 N-m (530 in.lbs.)
Angle Impact Driver



Capacity	Machine Screw: M4 - M8 (5/32 - 5/16") Standard Bolt: M4 - M12 (5/32 - 1/2") High Strength Bolt: M4 - M8 (5/32 - 5/16") Coarse thread (in length) : 22 - 75 mm (7/8 - 2-31/32")
Hex Shank	6.35 mm (1/4")
No Load Speed (RPM)	0 - 2,000
Impacts Per Minute (IPM)	0 - 3,000
Max Fastening Torque	60 N-m (530 in.lbs.)
Dimensions (L x W x H)	361 x 66 x 86 mm (14-1/4 x 2-5/8 x 3-3/8")
Net weight	1.2 - 1.6 kg (2.7 - 3.6 lbs.)

TL065D Cordless Angle Impact Wrench 12V max

12V max CXT Li-Ion Cordless
60 N-m (530 in.lbs.)
Angle Impact Wrench



Capacity	Standard Bolt: M4 - M12 (5/32 - 1/2") High Strength Bolt: M4 - M8 (5/32 - 5/16")
Square Drive	9.5 mm (3/8")
No Load Speed (RPM)	0 - 2,000
Impacts Per Minute (IPM)	0 - 3,000
Max Fastening Torque	60 N-m (530 in.lbs.)
Dimensions (L x W x H)	361 x 66 x 86 mm (14-1/4 x 2-5/8 x 3-3/8")
Net weight	1.2 - 1.6 kg (2.7 - 3.6 lbs.)

WR100D Cordless Ratchet Wrench 12V max

12Vmax CXT Li-Ion Cordless
47.5 N-m (420 in.lbs.)
Ratchet Wrench



Capacity	Standard Bolt: M5 - M12 (3/16 - 1/2") High Strength Bolt: M5 - M10 (3/16 - 3/8")
Square Drive	9.5 / 6.35 mm (3/8 / 1/4")
No Load Speed (RPM)	0 - 800
Max Fastening Torque	47.5 N-m (420 in.lbs.)
Flats Width	13 mm (1/2")
Angle Head Size	Diameter: 31 mm (1-7/32") Height: 25.5 mm (1")
Dimensions (L x W x H)	w/ BL1016/BL1021B : 341 x 67 x 63 mm (13-7/16 x 2-5/8 x 2-1/2")
Net weight	1.0 - 1.2 kg (2.3 - 2.7 lbs.)