

MVC-F80 VAS (92kg)




MVC-T90 VAS (108kg)



MVC-F80 (78kg)



MVC-T90 (91kg)



MVC-T100D (103kg)



Increased Weight (kg)

model	Water Tank	Cart	Folding Handle	VAS Handle
MVC-40H	+6	nil	standard	nil
MVC-40HR	+6	nil	standard	nil
MVC-50H	+6	nil	+1	nil
MVC-e60	+8	+2	nil	standard
MVC-F60H	+8	+2	nil	+5
MVC-F70H	+8	+2	nil	nil
MVC-F80H	+9	+2	nil	+3
MVC-T90H	+10	+4	nil	+3
MVC-T100D	+10	+4	nil	+3

*The weight of tank is 50% of water.
ex.) MVC-F60H with Tank & Cart & VAS = increased "15kg"

MVC Specifications

model	weight (kg)	dimensions (mm)	plate size (mm)	vibrating frequency Hz (V.P.M.)	centrifugal force (max) kN (kgf)	max.traveling speed (m/min)	max.limited gradeability (%)	power source kW (PS)
MVC-40H	50	H : 920 H1: 610 L : 910	W: 295 L1: 420	103 (6,200)	7.2 (730)	25	35	Honda GX100 gasoline max. output 2.1 (2.9)
MVC-40HR	51	H : 920 H1: 620 L : 910	W: 295 L1: 420	103 (6,200)	7.2 (730)			Honda GXR120 gasoline max. output 2.3 (3.1)
MVC-50H	59	H : 920 H1: 545 L : 915	W: 345 L1: 460	97 (5,800)	9.8 (1,000)			Honda GX120 gasoline max. output 2.4 (3.3)
MVC-F60H	65	H : 865 H1: 580 L : 925	W: 350 L1: 510	93 (5,600)	10.1 (1,030)			Honda GX160 gasoline max. output 3.6 (4.9)
MVC-F70H	73		W: 420 L1: 510		12.0 (1,220)			
MVC-F80H	78		W: 450 L1: 570		13.7 (1,400)			
MVC-T90H	91	H : 825 H1: 560 L : 1,100	W: 500 L1: 525	100 (6,000)	15.0 (1,530)			Yanmar L48N diesel max. output 3.5 (4.7)
MVC-T100D	103	H : 825 H1: 650 L : 1,100						