



มาคิต้า

MAKITA POWER TOOLS

เครื่องมือไฟฟ้า “มาคิต้า”

HR2811FT Combination Hammer

28 mm (1-1/8") 2.9 J Combination Hammer, SDS-PLUS Bits, Quick Change Drill Chuck, LED Light



Quick change drill chuck



Continuous rating Input	800W
Impact Energy	EPTA-Procedure 05/2009: 2.9 J
Capacity	Concrete (w/ TCT Bit): 28 mm (1-1/8") Steel: 13 mm (1/2")
	Wood: 32 mm (1-1/4") Wood (Self-Feed Bit): 32 mm (1-1/4") Masonry: 28 mm (1-1/4")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Blows Per Minute (BPM)	0 - 4,500
No Load Speed (RPM)	0 - 1,100
Dimensions (L x W x H)	345 x 89 x 225 mm (13-5/8 x 3-1/2 x 8-7/8")
Net weight	3.6 - 3.9 kg (8 - 8.6 lbs.)
Power supply cord	2.5 m (8.2 ft)

HR3530 Rotary Hammer

35 mm (1-3/8") 6.2 J Rotary Hammer, 19 mm Hex Shank



Continuous rating Input	1,010W
Capacity	Concrete (w/ TCT Bit): 35 mm (1-3/8") Masonry: 35 mm (1-3/8")
Blows Per Minute (BPM)	3,100
No Load Speed (RPM)	760
Dimensions (L x W x H)	374 x 100 x 243 mm (14-3/4 x 3-15/16 x 9-9/16")
Net weight	5.8 kg (12.8 lbs.)
Power supply cord	5.0 m (16.4 ft)

HR4030C Rotary Hammer

40 mm (1-9/16") 9.2 J Rotary Hammer, 17 mm Hex Shank



Continuous rating Input	1,100W
Capacity	Concrete (w/ TCT Bit): 40 mm (1-9/16") Masonry: 40 mm (1-9/16")
Blows Per Minute (BPM)	1,300 - 2,600
No Load Speed (RPM)	230 - 460
Dimensions (L x W x H)	413 x 107 x 247 mm (16-1/4 x 4-1/4 x 9-3/4")
Net weight	6.9 kg (15.2 lbs.)
Power supply cord	5.0 m (16.4 ft)

HR5202C Rotary Hammer

52 mm (2-1/16") 19.1 J Rotary Hammer, SDS-MAX Bits



Continuous rating Input	1,510W
Impact Energy	EPTA-Procedure 05/2009: 19.1 J
Capacity	Concrete (w/ TCT Bit): 52 mm (2") Masonry: 52 mm (2")
Blows Per Minute (BPM)	1,100 - 2,250
No Load Speed (RPM)	150 - 310
Dimensions (L x W x H)	599 x 134 x 287 mm (23-1/2 x 5-1/4 x 11-1/4")
Net weight	10.9 - 11.1 kg (24.1 - 24.4 lbs.)
Power supply cord	5.0 m (16.4 ft)

HR3200C Combination Hammer

32 mm (1-1/4") 5.1 J Combination Hammer, SDS-PLUS Bits



Continuous rating Input	850W
Impact Energy	EPTA-Procedure 05/2009: 5.1 J
Capacity	Concrete (w/ TCT Bit): 32 mm (1-1/4") Steel: 13 mm (1/2")
	Wood: 32 mm (1-1/4") Wood (Self-Feed Bit): 32 mm (1-1/4") Masonry: 32 mm (1-1/4")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Blows Per Minute (BPM)	1,650 - 3,300
No Load Speed (RPM)	315 - 630
Dimensions (L x W x H)	398 x 108 x 239 mm (15-5/8 x 4-1/4 x 9-3/8")
Net weight	4.8 - 5.2 kg (10.5 - 11.5 lbs.)
Power supply cord	5.0 m (16.4 ft)

HR4002 Rotary Hammer

40 mm (1-9/16") 6.1 J Rotary Hammer, SDS-MAX Bits



Continuous rating Input	1,050W
Impact Energy	EPTA-Procedure 05/2009: 6.1 J
Capacity	Concrete (w/ TCT Bit): 40 mm (1-9/16") Masonry: 40 mm (1-9/16")
Blows Per Minute (BPM)	2,500
No Load Speed (RPM)	680
Dimensions (L x W x H)	458 x 114 x 256 mm (18 x 4-1/2 x 10-1/8")
Net weight	6.6 - 6.8 kg (14.6 - 15 lbs.)
Power supply cord	5.0 m (16.4 ft)

HR4501C Rotary Hammer

45 mm (1-3/4") 10.1 J Rotary Hammer, SDS-MAX Bits



Continuous rating Input	1,350W
Impact Energy	EPTA-Procedure 05/2009: 10.1 J
Capacity	Concrete (w/ TCT Bit): 45 mm (1-3/4") Masonry: 45 mm (1-3/4")
Blows Per Minute (BPM)	1,250 - 2,750
No Load Speed (RPM)	130 - 280
Dimensions (L x W x H)	458 x 121 x 288 mm (18 x 4-3/4 x 11-3/8")
Net weight	8.2 - 8.4 kg (18.1 - 18.5 lbs.)
Power supply cord	5.0 m (16.4 ft)

HR5212C Rotary Hammer

52 mm (2-1/16") 20.0 J AVT SOFT NO LOAD Rotary Hammer, SDS-MAX Bits



Continuous rating Input	1,510W
Impact Energy	EPTA-Procedure 05/2009: 20 J
Capacity	Concrete (w/ TCT Bit): 52 mm (2") Masonry: 52 mm (2")
Blows Per Minute (BPM)	1,100 - 2,250
No Load Speed (RPM)	150 - 310
Dimensions (L x W x H)	599 x 140 x 287 mm (23-1/2 x 5-1/2 x 11-1/4")
Net weight	11.9 - 12 kg (26.2 - 26.5 lbs.)
Power supply cord	5.0 m (16.4 ft)

HR3210C Combination Hammer

32 mm (1-1/4") 5.0 J AVT Combination Hammer, SDS-PLUS Bits



AVT



Continuous rating Input	850W
Impact Energy	EPTA-Procedure 05/2009: 5.1 J
Capacity	Concrete (w/ TCT Bit): 32 mm (1-1/4") Steel: 13 mm (1/2")
	Wood: 32 mm (1-1/4") Wood (Self-Feed Bit): 32 mm (1-1/4") Masonry: 32 mm (1-1/4")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Blows Per Minute (BPM)	1,650 - 3,300
No Load Speed (RPM)	315 - 630
Dimensions (L x W x H)	398 x 108 x 239 mm (15-5/8 x 4-1/4 x 9-3/8")
Net weight	4.8 - 5.2 kg (10.5 - 11.5 lbs.)
Power supply cord	5.0 m (16.4 ft)

HR4013C Rotary Hammer

40 mm (1-9/16") 8.0 J AVT SOFT NO LOAD Rotary Hammer, SDS-MAX Bits



AVT SOFT NOLOAD



Continuous rating Input	1,100W
Impact Energy	EPTA-Procedure 05/2009: 8 J
Capacity	Concrete (w/ TCT Bit): 40 mm (1-9/16") Masonry: 40 mm (1-9/16")
Blows Per Minute (BPM)	1,450 - 2,900
No Load Speed (RPM)	250 - 500
Dimensions (L x W x H)	479 x 112 x 263 mm (18-11/16 x 4-3/8 x 10-3/8")
Net weight	6.8 - 6.9 kg (14.9 - 15.3 lbs.)
Power supply cord	5.0 m (16.4 ft)

HR4511C Rotary Hammer

45 mm (1-3/4") 9.4 J AVT Rotary Hammer, SDS-MAX Bits



AVT



Continuous rating Input	1,350W
Impact Energy	EPTA-Procedure 05/2009: 9.4 J
Capacity	Concrete (w/ TCT Bit): 45 mm (1-3/4") Masonry: 45 mm (1-3/4")
Blows Per Minute (BPM)	1,250 - 2,750
No Load Speed (RPM)	130 - 280
Dimensions (L x W x H)	458 x 136 x 288 mm (18 x 5-3/8 x 11-3/8")
Net weight	9 - 9.1 kg (19.8 - 20.1 lbs.)
Power supply cord	5.0 m (16.4 ft)

HM0810T Demolition Hammer

7.2 J Demolition Hammer, Sliding Chuck, 17 mm Hex shank



Continuous rating Input	900W
Impact Energy	EPTA-Procedure 05/2009: 7.2 J
Blows Per Minute (BPM)	2,900
Overall Length	428 mm (16-7/8")
Net weight	6.3 kg (13.9 lbs.)
Power supply cord	5.0 m (16.4 ft)