



มาคิต้า

MAKITA POWER TOOLS

เครื่องมือไฟฟ้า “มาคิต้า”

DA4000LR Angle Drill

13 mm (1/2") 710 W Angle Drill with Keyed Chuck



Continuous rating Input Capacity	710W Steel: 13 mm (1/2")
Wood (Self-Feed Bit):	118 mm (4-5/8")
Wood (Self-Feed Bit) Hi:	65 mm (2-9/16")
Wood (Self-Feed Bit) Lo:	118 mm (4-5/8")
Wood (Hole Saw) Hi:	114 mm (4-1/2")
Wood (Hole Saw) Lo:	152 mm (6")
Chuck Capacity	2 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High: 0 - 900 Low: 0 - 400
Overall Length	413 mm (16-1/4")
Net weight	4 kg (8.9 lbs.)
Power supply cord	2.5 m (8.2 ft)

6412 Drill

10 mm (3/8") 450 W Variable Speed Reversing Drill with Keyed Chuck



Continuous rating Input Capacity	450W Steel: 10 mm (3/8") Wood: 25 mm (1")
Wood (Self-Feed Bit):	50 mm (2")
1.5 - 10 mm (1/16 - 3/8")	
Chuck Capacity	0 - 3,400
No Load Speed (RPM)	228 x 64 x 183 mm (9 x 2-1/2 x 7-1/4")
Dimensions (L x W x H)	1.3 kg (2.9 lbs.)
Net weight	2.0 m (6.6 ft)
Power supply cord	

DP4010 2-Speed Drill

13 mm (1/2") 720 W Variable 2-Speed Reversing Drill with Keyed Chuck



Continuous rating Input Capacity	720W Steel: 13 mm (1/2") Steel Hi: 8 mm (5/16") Steel Lo: 13 mm (1/2") Wood Hi: 25 mm (1") Wood Lo: 40 mm (1-9/16") Wood (Self-Feed Bit): 90 mm (3-1/2")
Chuck Capacity	1.5 - 13.0 mm (1/16 - 1/2")
No Load Speed (RPM)	High: 0 - 2,900 Low: 0 - 1,200
Dimensions (L x W x H)	347 x 70 x 220 mm (13-5/8 x 2-3/4 x 8-5/8")
Net weight	2.3 kg (5 lbs.)
Power supply cord	2.5 m (8.2 ft)

HP0300 Hammer Driver Drill

10 mm (3/8") 320 W Hammer Driver Drill with Keyless Chuck



Continuous rating Input Capacity	320W Concrete: 8 mm (5/16") Steel: 10 mm (3/8") Wood: 28 mm (1-1/8")
1.0 - 10 mm (1/32 - 3/8")	
Chuck Capacity	High: 0 - 22,500 Low: 0 - 6,750
Blows Per Minute (BPM)	High: 0 - 1,500 Low: 0 - 450
No Load Speed (RPM)	42.0 N-m (370 in.lbs.)
Max Fastening Torque	235 x 67 x 206 mm (9-1/4 x 2-5/8 x 8-1/8")
Max Lock Torque	1.3 kg (2.8 lbs.)
Dimensions (L x W x H)	2.5 m (8.2 ft)
Net weight	
Power supply cord	

DF0300 Driver Drill

10 mm (3/8") 320 W Driver Drill with Keyless Chuck



Continuous rating Input Capacity	320W Steel: 10 mm (3/8") Wood: 28 mm (1-1/8")
1.0 - 10 mm (1/32 - 3/8")	
Chuck Capacity	High: 0 - 1,500 Low: 0 - 450
No Load Speed (RPM)	42.0 N-m (370 in.lbs.)
Max Fastening Torque	220 x 67 x 206 mm (8-5/8 x 2-5/8 x 8-1/8")
Max Lock Torque	1.2 kg (2.7 lbs.)
Dimensions (L x W x H)	2.5 m (8.2 ft)
Net weight	
Power supply cord	

6413 Drill

10 mm (3/8") 450 W Variable Speed Reversing Drill with Keyless Chuck



Continuous rating Input Capacity	450W Steel: 10 mm (3/8") Wood: 25 mm (1") Wood (Self-Feed Bit): 50 mm (2")
1.5 - 10 mm (1/16 - 3/8")	
Chuck Capacity	0 - 3,400
No Load Speed (RPM)	234 x 64 x 183 mm (9-1/4 x 2-1/2 x 7-1/4")
Dimensions (L x W x H)	1.3 kg (2.9 lbs.)
Net weight	2.0 m (6.6 ft)
Power supply cord	

DP4011 2-Speed Drill

13 mm (1/2") 720 W Variable 2-Speed Reversing Drill with Keyless Chuck



Continuous rating Input Capacity	720W Steel: 13 mm (1/2") Steel Hi: 8 mm (5/16") Steel Lo: 13 mm (1/2") Wood Hi: 25 mm (1") Wood Lo: 40 mm (1-9/16") Wood (Self-Feed Bit): 90 mm (90°)
Chuck Capacity	1.5 - 13.0 mm (1/16 - 1/2")
No Load Speed (RPM)	High: 0 - 2,900 Low: 0 - 1,200
Dimensions (L x W x H)	347 x 70 x 220 mm (13-5/8 x 2-3/4 x 8-5/8")
Net weight	2.3 kg (5 lbs.)
Power supply cord	2.5 m (8.2 ft)

HP1230 Hammer Drill

12 mm (15/32") 400 W Hammer Drill with Keyed Chuck



Continuous rating Input Capacity	400W Concrete: 12 mm (15/32") Steel: 10 mm (3/8") Wood: 15 mm (9/16") Wood (Self-Feed Bit): 30 mm (1-3/16") Masonry: 12 mm (15/32")
1.5 - 10 mm (1/16 - 3/8")	
Chuck Capacity	High: 0 - 31,900 Low: 0 - 2,900
Blows Per Minute (BPM)	239 x 67 x 188 mm (9-3/8 x 2-5/8 x 7-3/8")
No Load Speed (RPM)	1.7 kg (3.7 lbs.)
Dimensions (L x W x H)	2.0 m (6.6 ft)
Net weight	
Power supply cord	

DP2010 High Speed Drill

6.5 mm (1/4") 370 W High Speed Variable Speed Reversing Drill with Keyed Chuck



Continuous rating Input Capacity	370W Steel: 6.5 mm (1/4") Wood: 15 mm (9/16") Wood (Self-Feed Bit): 30 mm (1-3/16")
0.5 - 6.5 mm (1/64 - 1/4")	
Chuck Capacity	0 - 4,200
No Load Speed (RPM)	209 x 64 x 175 mm (8-1/4 x 2-1/2 x 6-7/8")
Dimensions (L x W x H)	1 kg (2.2 lbs.)
Net weight	2.0 m (6.6 ft)
Power supply cord	

DA3010 Angle Drill

10 mm (3/8") 450 W Angle Drill with Keyed Chuck



Continuous rating Input Capacity	450W Steel: 10 mm (3/8") Wood: 25 mm (1") Wood (Self-Feed Bit): 50 mm (2")
1.5 - 10 mm (1/16 - 3/8")	
Chuck Capacity	0 - 2,400
No Load Speed (RPM)	270 mm (10-5/8")
Overall Length	1.6 kg (3.5 lbs.)
Net weight	2.5 m (8.2 ft)
Power supply cord	

DP4700 Drill

13 mm (1/2")



Continuous rating input Capacity	510W Steel: 13 mm (1/2") Wood: 36 mm (1-3/8")
0-550	
No Load Speed (RPM)	275 mm (10-7/8")
Overall Length	2.2 kg (4.8 lbs.)
Net weight	2.5 m (8.2 ft)
Power supply cord	

HP1630 Hammer Drill

16 mm (5/8") 710 W Hammer Drill with Keyed Chuck



Continuous rating Input Capacity	710W Concrete: 16 mm (5/8") Steel: 13 mm (1/2") Wood: 30 mm (1-3/16") Wood (Self-Feed Bit): 60 mm (2-3/8") Masonry: 16 mm (5/8")
1.5 - 13 mm (1/16 - 1/2")	
Chuck Capacity	0 - 48,000
Blows Per Minute (BPM)	0 - 3,200
No Load Speed (RPM)	296 x 75 x 204 mm (11-5/8 x 2-15/16 x 8")
Dimensions (L x W x H)	2.1 kg (4.6 lbs.)
Net weight	2.0 m (6.6 ft)
Power supply cord	