

เบรกและเกียร์

Universal strut spring compressor

ชุดเครื่องมือถอดสปริงแบบขาทำมุม

- This tool fits a wide range of struts without the inconvenience of special adaptor shoes.
- Tool compresses springs of 4" to 8" OD. with wire diameters of 7/16" to 11/16". Works both by hand or impact wrench.
- The jaws of the compressor are held in place by safety locking pins.
- Use most of spring compressor quickly and easily on the bench or on the vehicle.






| KT Code | Model | Weight (g) | Price |
|------------|-------|------------|----------|
| F131-62702 | 62702 | 9350 | 10,130.- |

CV Boot clamp pliers

คีมย้ำหัวเข็มขัด รัศยางค์บูทเพลลา (สายรัดแบบไม่มีหู)

A sturdy tool, works on earless-type clamps including those found on GM inboard CV joint.

| KT Code | Model | Weight (g) | Price |
|------------|-------|------------|-------|
| F131-62519 | 62519 | 320 | 590.- |


39pc Turnbuckle for shock absorber's top lid

ชุดข้อต่อจับแกนโช้คอัพ 39 ชิ้น

- The complete sizes for using of most kinds of cars.

Contents:

- 5pc external sockets 10.5, 12.5, 14, 14.5(14.5x5), 14.5(14.5x3)mm
- 9pc external sockets 14, 16, 17, 18, 19, 21, 22, 24, 27mm
- 9pc central sockets 4, 5.2, 6, 6.3, 7, 8, 9, 10, 12mm
- 2pc central sockets 5, 10mm
- 4pc central sockets 8, 9, 10, 11mm
- 4pc central sockets 5, 6, 7, 8mm
- 3pc central sockets 3, 3.5, 4mm
- 1pc central socket M12
- 2pc central sockets T50, T60



- Apply to : VW, AUDI, M-BENZ, AUSTIN MAESTRO, HONDA, NISSAN, SEAT, FIAT, FORD, ROVER, OPEL, PEUGEOT, RENAULT, CITROEN, TOYOTA, CHRYSLER, BMW, VOLVO.

CV Joint boot clamp pliers

คีมย้ำหัวเข็มขัด รัศยางค์บูทเพลลา (สายรัดชนิดมีหู)

For ear type clamps, fits late model GM CV joint boots, also installs PERMA-QUICK type clamps quickly and easily use for filter, cooling system and vacuum lines.







| KT Code | Model | Weight (g) | Price |
|------------|-------|------------|-------|
| F131-62520 | 62520 | 380 | 620.- |

CV Dust boot clamp installer with cutter

ตัวรัดเหล็กรัศยางค์บูทเพลลา พร้อมคัตเตอร์

- Use 1/2" socket wrench to wind and crimp by hand tool is easily disengaged from the band after the band is tightened.
- Cut off easily with built in cutting arm without any other tool.


| KT Code | Model | Weight (g) | Price |
|------------|-------|------------|----------|
| F131-939T1 | 939T1 | 6250 | 14,090.- |

CV Dust boot clamp installer with cutter

ตัวรัดเหล็กรัศยางค์บูทเพลลา พร้อมคัตเตอร์

- Use 1/2" socket wrench to wind and crimp by hand tool is easily disengaged from the band after the band is tightened.
- Cut off easily with built in cutting arm without any other tool.





| KT Code | Model | Weight (g) | Price |
|------------|-------|------------|---------|
| F131-62521 | 62521 | 510 | 1,250.- |

