

## MAKITA POWER TOOLS เครื่องมือไฟฟ้า “มากที่สุด”



มากที่สุด

### GA021G Cordless Angle Grinder 40V max

40Vmax XGT BL AWS AFT Cordless Angle Grinder, Anti-Restart Function, Electric Brake, Slide Switch Lock-On



Wheel Diameter	100 mm (4")
Hole Diameter	16 mm (5/8")
No Load Speed (RPM)	3,000 - 8,500
Dimensions (L x W x H)	w/ BL4040: 425 x 117 x 162 mm (16-3/4 x 4-5/8 x 6-3/8") w/ BL4020 / BL4025: 413 x 117 x 150 mm (16-1/4 x 4-5/8 x 5-7/8")
Net weight	2.8 - 3.4 kg (6.2 - 7.5 lbs.)

### GA027G Cordless Angle Grinder 40V max

40Vmax XGT BL AWS AFT Cordless Angle Grinder, Anti-Restart Function, Electric Brake, Paddle Switch



Wheel Diameter	100 mm (4")
Hole Diameter	16 mm (5/8")
No Load Speed (RPM)	3,000 - 8,500
Dimensions (L x W x H)	w/ BL4040 : 425 x 117 x 162 mm (16-3/4 x 4-5/8 x 6-3/8") w/ BL4020 / BL4025 : 413 x 117 x 150 mm (16-1/4 x 4-5/8 x 5-7/8")
Net weight	2.9 - 3.4 kg (6.4 - 7.5 lbs.)

### GA005G Cordless Angle Grinder 40V max

40Vmax XGT BL AFT Cordless Angle Grinder, Anti-Restart Function, Electric Brake, Slide Switch Lock-On



Wheel Diameter	125 mm (5")
Hole Diameter	22.23 mm (7/8")
No Load Speed (RPM)	8,500
Dimensions (L x W x H)	w/ BL4040: 410 x 140 x 168 mm (16-1/8 x 5-1/2 x 6-5/8") w/ BL4020 / BL4025: 398 x 140 x 156 mm (15-5/8 x 5-1/2 x 6-1/8")
Net weight	2.9 - 3.6 kg (6.4 - 7.9 lbs.)

### GA008G Cordless Angle Grinder 40V max

40Vmax XGT BL AFT Cordless Angle Grinder, Anti-Restart Function, Slide Switch Lock-On



Wheel Diameter	125 mm (5")
Hole Diameter	22.23 mm (7/8")
No Load Speed (RPM)	8,500
Dimensions (L x W x H)	w/ BL4040: 410 x 140 x 165 mm (16-1/8 x 5-1/2 x 6-1/2") w/ BL4020 / BL4025: 398 x 140 x 152 mm (15-5/8 x 5-1/2 x 6")
Net weight	2.9 - 3.5 kg (6.4 - 7.7 lbs.)

### GA013G Cordless Angle Grinder 40V max

40Vmax XGT BL AFT Cordless Angle Grinder, Anti-Restart Function, Electric Brake, Paddle Switch



Wheel Diameter	125 mm (5")
Hole Diameter	22.23 mm (7/8")
No Load Speed (RPM)	8,500
Dimensions (L x W x H)	w/ BL4040: 410 x 140 x 168 mm (16-1/8 x 5-1/2 x 6-5/8") w/ BL4020 / BL4025: 398 x 140 x 156 mm (15-5/8 x 5-1/2 x 6-1/8")
Net weight	3.0 - 3.6 kg (6.6 - 7.9 lbs.)

### GA023G Cordless Angle Grinder 40V max

40Vmax XGT BL AWS AFT Cordless Angle Grinder, Anti-Restart Function, Electric Brake, Slide Switch Lock-On



Wheel Diameter	125 mm (5")
Hole Diameter	22.23 mm (7/8")
No Load Speed (RPM)	3,000 - 8,500
Dimensions (L x W x H)	w/ BL4040: 425 x 140 x 168 mm (16-3/4 x 5-1/2 x 6-5/8") w/ BL4020 / BL4025: 413 x 140 x 156 mm (16-1/4 x 5-1/2 x 6-1/8")
Net weight	3.0 - 4.4 kg (6.6 - 9.7 lbs.)

### GA029G Cordless Angle Grinder 40V max

40Vmax XGT BL AWS AFT Cordless Angle Grinder, Anti-Restart Function, Electric Brake, Paddle Switch



Wheel Diameter	125 mm (5")
Hole Diameter	22.23 mm (7/8")
No Load Speed (RPM)	3,000 - 8,500
Dimensions (L x W x H)	w/ BL4040 : 425 x 140 x 168 mm (16-3/4 x 5-1/2 x 6-5/8") w/ BL4020 / BL4025 : 413 x 140 x 156 mm (16-1/4 x 5-1/2 x 6-1/8")
Net weight	3.0 - 4.5 kg (6.6 - 9.9 lbs.)

### LS003G Cordless Slide Compound Miter Saw 40V max

40Vmax XGT BL AWS Cordless 305 mm (12") Slide Compound Miter Saw, LED Light



Blade Diameter	305 mm (12")
Hole Diameter	25.4, 30 mm (1, 1-3/16")
Miter Angle	60° L 60° R
Bevel Angle	48° L 48° R
Max Cutting Capacity	0° Miter: 107 x 363 mm (4-1/4 x 14-1/4") 45° Miter, L/R: 107 x 255 mm (4-1/4 x 10")
No Load Speed (RPM)	3,600
Dimensions (L x W x H)	898 x 690 x 725 mm (35-1/4 x 27-1/4 x 28-1/2")
Net weight	30.5 - 31.1 kg (67.2 - 68.6 lbs.)

### LS004G Cordless Slide Compound Miter Saw 40V max

40Vmax XGT BL AWS Cordless 260 mm (10-1/4") Slide Compound Miter Saw, LED Light



Blade Diameter	260 mm (10-1/4")
Hole Diameter	25.4, 30 mm (1, 1-3/16")
Miter Angle	60° L 60° R
Bevel Angle	48° L 48° R
Max Cutting Capacity	0° Miter: 91 x 279 mm (3-5/8 x 11") 45° Miter, L/R: 91 x 197 mm (3-5/8 x 7-3/4")
No Load Speed (RPM)	3,600
Dimensions (L x W x H)	805 x 644 x 660 mm (31-5/8 x 25-3/8 x 26")
Net weight	26.6 - 27.2 kg (58.6 - 60.0 lbs.)

### LS002G Cordless Slide Compound Miter Saw 40V max

40Vmax XGT BL AWS Cordless 216 mm (8-1/2") Slide Compound Miter Saw, LED Light



Blade Diameter	216 mm (8-1/2")
Hole Diameter	25.4, 30 mm (1, 1-3/16")
Miter Angle	60° / 60° L 60, 60° R
Bevel Angle	48° / 48° L 48, 48° R
Max Cutting Capacity	0° Miter: 70 x 312 mm (2-3/4 x 12-1/4") 45° Miter, L/R: 70 x 220 mm (2-3/4 x 8-5/8")
No Load Speed (RPM)	4,800
Dimensions (L x W x H)	702 x 551 x 557 mm (27-5/8 x 21-3/4 x 22")
Net weight	16.4 - 17.0 kg (36.2 - 37.6 lbs.)

### RS002G Cordless Rear Handle Saw 40V max

40Vmax XGT BL AWS Cordless 260 mm (10-1/4") Magnesium Rear Handle Saw, Electric Brake, Soft Start



Blade Diameter	260 mm (10-1/4")
Hole Diameter	15.88, 25, 25.4, 30 mm (5/8, 1, 1, 1-3/16")
Max Cutting Capacity	0°: 95 mm (3-3/4") 45°: 70 mm (2-3/4") 56°: 54.5 mm (2-1/8")
No Load Speed (RPM)	4,000
Dimensions (L x W x H)	489 x 193 x 309 mm (19-1/4 x 7-5/8 x 12-1/8")
Net weight	5.7 - 6.3 kg (12.6 - 13.9 lbs.)

### RS001G Cordless Rear Handle Saw 40V max

40Vmax XGT BL ADT Cordless 185 mm (7-1/4") Magnesium Rear Handle Saw, Electric Brake, Soft Start



Blade Diameter	185 mm (7-1/4")
Hole Diameter	15.88, 19, 20, 30 mm (5/8, 3/4, 13/16, 1-3/16")
Max Cutting Capacity	0°: 65 mm (2-9/16") 45°: 45 mm (1-3/4") 53°: 38 mm (1-1/2")
No Load Speed (RPM)	6,400
Dimensions (L x W x H)	446 x 196 x 270 mm (17-1/2 x 7-3/4 x 10-5/8")
Net weight	5.0 - 5.6 kg (11.0 - 12.3 lbs.)