

POWER TOOLS & ABRASIVES

MAKITA POWER TOOLS เครื่องมือไฟฟ้า “มาคิต้า”



มาคิต้า

HM1201 Demolition Hammer

13.0 J: Makita (Standard) Demolition Hammer,
21 mm Hex Shank



Continuous rating Input	1,130W
Blows Per Minute (BPM)	2,000
Overall Length	480 mm (18-7/8")
Net weight	9.1 kg (20.1 lbs.)
Power supply cord	5.0 m (16.4 ft)

HM1306 Demolition Hammer

21.7 J Demolition Hammer,
30 mm Hex Shank



Continuous rating Input	1,510W
Impact Energy	EPTA-Procedure 05/2009: 21.7 J
Blows Per Minute (BPM)	1,450
Dimensions (L x W x H)	652 x 121 x 231 mm (25-3/4 x 4-3/4 x 9-1/8")
Net weight	15.1 kg (33.3 lbs.)
Power supply cord	5.0 m (16.4 ft)

HM1501 Electric Breaker

48.1 J Electric Breaker, 30 mm Hex Shank



Continuous rating Input	1,850W
Impact Energy	EPTA-Procedure 05/2009: 48.1 J
Blows Per Minute (BPM)	1,300
Dimensions (L x W x H)	781 x 130 x 266 mm (30-3/4 x 5-1/8 x 10-1/2")
Net weight	18.4 kg (40.6 lbs.)
Power supply cord	4.0 m (13.1 ft)

HM1812 Electric Breaker

72.8 J AVT SOFT NO LOAD Electric Breaker, 28.6 mm Hex Shank



Continuous rating Input	1,510W
Impact Energy	EPTA-Procedure 05/2009: 19.1 J
Capacity	Concrete (w/TCT Bit): 52 mm (2") Masonry: 52 mm (2")
Blows Per Minute (BPM)	1,100 - 2,250
No Load Speed (RPM)	150 - 310
Dimensions (L x W x H)	599 x 134 x 287 mm (23-1/2 x 5-1/4 x 11-1/4")
Net weight	10.9 - 11.1 kg (24.1 - 24.4 lbs.)
Power supply cord	5.0 m (16.4 ft)

HM1203C Demolition Hammer

19.1 J Demolition Hammer,
SDS-MAX Bits



Continuous rating Input	1,510W
Impact Energy	EPTA-Procedure 05/2009: 19.1 J
Blows Per Minute (BPM)	950 - 1,900
Dimensions (L x W x H)	576 x 128 x 265 mm (22-3/4 x 5 x 10-3/8")
Net weight	9.7 kg (21.5 lbs.)
Power supply cord	5.0 m (16.4 ft)

HM1307C Electric Breaker

25.5 J Electric Breaker,
30 mm Hex Shank



Continuous rating Input	1,510W
Impact Energy	EPTA-Procedure 05/2009: 25.5 J
Blows Per Minute (BPM)	730 - 1,450
Dimensions (L x W x H)	715 x 129 x 266 mm (28-1/8 x 5-1/8 x 10-1/2")
Net weight	15.3 kg (33.8 lbs.)
Power supply cord	5.0 m (16.4 ft)

HM1511 Electric Breaker

48.9 J AVT SOFT NO LOAD Electric Breaker,
30 mm Hex Shank



Continuous rating Input	1,850W
Impact Energy	EPTA-Procedure 05/2009: 48.9 J
Blows Per Minute (BPM)	1,300
Dimensions (L x W x H)	781 x 130 x 266 mm (30-3/4 x 5-1/8 x 10-1/2")
Net weight	19.2 kg (42.3 lbs.)
Power supply cord	4.0 m (13.1 ft)

6301 Drill

13 mm (1/2")



Continuous rating input	700W
Capacity	Steel: 13 mm (1/2") Wood: 30 mm (1-1/8")
No Load Speed (RPM)	1,300
	340 mm (13-3/8")
	2.8 kg (6.1 lbs.)
Power supply cord	2.5 m (8.2 ft)

HM1214C Demolition Hammer

19.9 J AVT SOFT NO LOAD Demolition
Hammer, SDS-MAX Bits



Continuous rating Input	1,510W
Impact Energy	EPTA-Procedure 05/2009: 19.9 J
Blows Per Minute (BPM)	950 - 1,900
Dimensions (L x W x H)	700 x 129 x 265 mm (27-1/2 x 5-1/8 x 10-3/8")
Net weight	12.3 kg (27.1 lbs.)
Power supply cord	5.0 m (16.4 ft)

HM1317C Electric Breaker

25.0 J AVT SOFT NO LOAD Electric
Breaker, 30 mm Hex Shank



Continuous rating Input	1,510W
Impact Energy	EPTA-Procedure 05/2009: 25 J
Blows Per Minute (BPM)	730 - 1,450
Dimensions (L x W x H)	715 x 129 x 266 mm (28-1/8 x 5-1/8 x 10-1/2")
Net weight	17 kg (37.5 lbs.)
Power supply cord	5.0 m (16.4 ft)

HM1802 Electric Breaker

71.4 J Electric Breaker, 28.6 mm Hex Shank



Continuous rating Input	2,000W
Impact Energy	EPTA-Procedure 05/2009: 71.4 J
Blows Per Minute (BPM)	870
Dimensions (L x W x H)	843 x 210 x 608 mm (33-1/4 x 8-1/4 x 24")
Net weight	29.4 kg (64.8 lbs.)
Power supply cord	5.0 m (16.4 ft)

6305 Drill

13 mm (1/2") 850 W Drill with Keyed Chuck



Continuous rating Input	850W
Capacity	Steel: 13 mm (1/2") Wood: 30 mm (1-3/16") Wood (Self-Feed Bit): 60 mm (2-3/8")
Chuck Capacity	2 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	1,450
Dimensions (L x W x H)	346 x 84 x 152 mm (13-5/8 x 3-5/16 x 6")
Net weight	2.8 kg (6.2 lbs.)
Power supply cord	2.5 m (8.2 ft)