

MAKITA POWER TOOLS เครื่องมือไฟฟ้า “มากิต้า”



มากิต้า

HR001G Cordless Combination Hammer 40V max

40Vmax XGT BL AFT AWS AVT
SOFT NO LOAD
Cordless 28 mm (1-1/8")
Combination Hammer,
SDS-PLUS Bits



XGT BL AFT AWS
AVT SOFT XPT



Impact Energy Capacity	EPTA-Procedure 05/2009: 2.8 J Concrete / Steel / Wood / Core Bit / Diamond Core Bit (Dry Type): 28 / 13 / 32 / 54 / 65 mm (1-1/8" / 1/2" / 1-1/4" / 2-1/8" / 2-9/16") Masonry: 28 mm (1-1/8") Wood (Self-Feed Bit): 32 mm (1-1/4")
Blows Per Minute (BPM)	0 - 5,000
No Load Speed (RPM)	0 - 980
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Dimensions (L x W x H)	w/ BL4020 / BL4025: 358 x 102 x 232 mm (14-1/8 x 4 x 9-1/8") w/ BL4040: 373 x 102 x 238 mm (14-3/4 x 4 x 9-3/8")
Net weight	3.9 - 4.6 kg (8.6 - 10.1 lbs.)

HR002G Cordless Combination Hammer 40V max

40Vmax XGT BL AFT AWS AVT
SOFT NO LOAD
Cordless 28 mm (1-1/8")
Combination Hammer,
SDS-PLUS Bits,
Quick Change Chuck



XGT BL AFT AWS
AVT SOFT XPT



Impact Energy Capacity	EPTA-Procedure 05/2009: 2.9 J Concrete / Steel / Wood / Core Bit / Diamond Core Bit (Dry Type): 28 / 13 / 32 / 54 / 65 mm (1-1/8" / 1/2" / 1-1/4" / 2-1/8" / 2-9/16") Masonry: 28 mm (1-1/8") Wood (Self-Feed Bit): 32 mm (1-1/4")
Blows Per Minute (BPM)	0 - 5,000
No Load Speed (RPM)	0 - 980
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Dimensions (L x W x H)	w/ BL4020 / BL4025: 389 x 102 x 232 mm (15-1/4 x 4 x 9-1/8") w/ BL4040: 404 x 102 x 238 mm (15-7/8 x 4 x 9-3/8")
Net weight	4.1 - 4.6 kg (9.0 - 10.1 lbs.)

HR003G Cordless Combination Hammer 40V max

40Vmax XGT BL AVT
Cordless 28 mm (1-1/8")
Combination Hammer,
SDS-PLUS Bits



XGT BL AVT XPT



Impact Energy Capacity	EPTA-Procedure 05/2009: 2.8 J Concrete / Steel / Wood / Core Bit / Diamond Core Bit (Dry Type): 28 / 13 / 32 / 54 / 65 mm (1-1/8" / 1/2" / 1-1/4" / 2-1/8" / 2-9/16") Masonry: 28 mm (1-1/8") Wood (Self-Feed Bit): 32 mm (1-1/4")
Blows Per Minute (BPM)	0 - 5,000
No Load Speed (RPM)	0 - 980
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Dimensions (L x W x H)	w/ BL4020 / BL4025: 358 x 121 x 232 mm (14-1/8 x 4-3/4 x 9-1/8") w/ BL4040: 373 x 102 x 238 mm (14-3/4 x 4 x 9-3/8")
Net weight	3.9 - 4.6 kg (8.6 - 10.1 lbs.)

HR004G Cordless Combination Hammer 40V max

40Vmax XGT BL AVT
Cordless 28 mm (1-1/8")
Combination Hammer,
SDS-PLUS Bits,
Quick Change Chuck



XGT BL AVT XPT



Impact Energy Capacity	EPTA-Procedure 05/2009: 2.9 J Concrete / Steel / Wood / Core Bit / Diamond Core Bit (Dry Type): 28 / 13 / 32 / 54 / 65 mm (1-1/8" / 1/2" / 1-1/4" / 2-1/8" / 2-9/16") Masonry: 28 mm (1-1/8") Wood (Self-Feed Bit): 32 mm (1-1/4")
Blows Per Minute (BPM)	0 - 5,000
No Load Speed (RPM)	0 - 980
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Dimensions (L x W x H)	w/ BL4020 / BL4025: 389 x 102 x 232 mm (15-1/4 x 4 x 9-1/8") w/ BL4040: 404 x 102 x 238 mm (15-7/8 x 4 x 9-3/8")
Net weight	4.0 - 4.5 kg (8.8 - 9.9 lbs.)

HR005G Cordless Rotary Hammer 40V max

40Vmax XGT BL AFT AWS AVT SOFT NO LOAD Cordless 40 mm (1-9/16")
Rotary Hammer,
SDS-Max Bits,
Twin LED Lights



XGT BL AFT AWS AVT SOFT XPT



Impact Energy Capacity	EPTA-Procedure 05/2009: 8 J Concrete (w/ TCT Bit): 40 mm (1-9/16")
Blows Per Minute (BPM)	1,450 - 2,900
No Load Speed (RPM)	250 - 500
Dimensions (L x W x H)	w/ BL4020 / BL4025: 484 x 115 x 286 mm (19 x 4-1/2 x 11-1/4") w/ BL4040: 500 x 115 x 286 mm (19-3/4 x 4-1/2 x 11-1/4") w/ BL4050F: 520 x 115 x 305 mm (20-1/2 x 4-1/2 x 12")
Net weight	7.4 - 8.2 kg (16.3 - 18.1 lbs.)

HR006G Cordless Rotary Hammer 40V max x2

40Vmax X2 (80Vmax) XGT BL AFT AWS AVT SOFT NO LOAD Cordless
52 mm (2-1/16") 21.4 J
Rotary Hammer,
SDS-MAX Bits



XGT BL AFT AWS AVT SOFT XPT



Impact Energy Capacity	EPTA-Procedure 05/2009: 21.4 J Concrete (w/ TCT Bit): 52 mm (2-1/16")
Blows Per Minute (BPM)	1,100 - 2,250
No Load Speed (RPM)	150 - 310
Dimensions (L x W x H)	w/ BL4040: 610 x 140 x 337 mm (24 x 5-1/2 x 13-1/4") w/ BL4050F: 574 x 156 x 344 mm (22-5/8 x 6-1/8 x 13-1/2")
Net weight	12.9 - 14.3 kg (28.4 - 31.5 lbs.)

HR007G Cordless Combination Hammer 40V max

40Vmax XGT BL AFT AWS AVT Cordless 28 mm (1-1/8")
Combination Hammer,
SDS-PLUS Bits



XGT BL AFT AWS AVT XPT



Impact Energy Capacity	EPTA-Procedure 05/2009: 3.0 J Masonry: 28 mm (1-1/8")
Blows Per Minute (BPM)	0 - 5,000
No Load Speed (RPM)	0 - 980
Dimensions (L x W x H)	w/ BL4020 / BL4025: 458 x 101 x 234 mm (18 x 4 x 9-1/4") w/ BL4040: 473 x 101 x 240 mm (18-5/8 x 4 x 9-1/2") w/ BL4020 / BL4025: 182 x 86 x 275 mm (7-1/8 x 3-3/8 x 10-7/8") w/ BL4040: 182 x 86 x 282 mm (7-1/8 x 3-3/8 x 11-1/8")
Net weight	3.8 - 4.8 kg (8.4 - 10.6 lbs.)

HM001G Cordless Demolition Hammer 40V max

40Vmax XGT BL AWS AVT SOFT NO LOAD 9.4 J
Cordless Demolition Hammer, SDS-MAX Bits



XGT BL AWS AVT SOFT XPT



Impact Energy Capacity	EPTA-Procedure 05/2009: 9.4 J
Blows Per Minute (BPM)	0 - 2,650
Shank Diameter	18 mm (11/16")
Dimensions (L x W x H)	w/ BL4020 / BL4025: 481 x 113 x 258 mm (19 x 4-7/16 x 10-1/8") w/ BL4040: 496 x 113 x 258 mm (19-1/2 x 4-7/16 x 10-1/8") w/ BL4050F: 516 x 113 x 280 mm (20-3/4 x 4-7/16 x 11")
Net weight	6.3 - 7.1 kg (13.9 - 15.7 lbs.)

HM002G Cordless Demolition Hammer 40V max x2

40Vmax X2 (80Vmax) XGT BL AWS AVT SOFT NO LOAD 20.9 J
Demolition Hammer, SDS-MAX Bits



XGT BL AWS AVT SOFT XPT



Impact Energy Capacity	EPTA-Procedure 05/2009: 20.9 J
Blows Per Minute (BPM)	950 - 1,900
Shank Diameter	18 mm (11/16")
Dimensions (L x W x H)	w/ BL4020 / BL4025: 574 x 146 x 324 mm (22-5/8 x 5-3/4 x 12-3/4") w/ BL4040: 574 x 146 x 324 mm (22-5/8 x 5-3/4 x 12-3/4") w/ BL4050F: 574 x 156 x 344 mm (22-5/8 x 6-1/8 x 13-1/2")
Net weight	12.0 - 13.3 kg (26.5 - 29.3 lbs.)

HP001G Cordless Hammer Driver Drill 40V max

40Vmax XGT BL AFT Cordless
13 mm (1/2") 125 N-m (1,100 in.lbs.)
Hammer Driver Drill



XGT BL AFT XPT



Capacity	Steel: 20 mm (13/16") Wood (Auger-Bit): 50 mm (2") Wood (Self-Feed Bit): 76 mm (3") Sliding Board: 220 mm (8-5/8")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Impacts Per Minute (IPM)	High / Low: 0 - 39,000 / 0 - 9,750
No Load Speed (RPM)	High / Low: 0 - 2,600 / 0 - 650
Max Fastening Torque	Hard / Soft: 140 / 68 N-m (1,240 / 600 in.lbs.)
Max Lock Torque	125 N-m (1,100 in.lbs.)
Dimensions (L x W x H)	w/ BL4020 / BL4025: 182 x 86 x 275 mm (7-1/8 x 3-3/8 x 10-7/8") w/ BL4040: 182 x 86 x 282 mm (7-1/8 x 3-3/8 x 11-1/8")
Net weight	2.7 - 3.0 kg (6.0 - 6.6 lbs.)

HP002G Cordless Hammer Driver Drill 40V max

40Vmax XGT BL Brushless Cordless
13 mm (1/2") 65 N-m (580 in.lbs.)
Hammer Driver Drill



XGT BL XPT



Capacity	Steel / Wood (Auger Bit) / Wood (Self-Feed Bit) / Wood (Hole Saw) / Masonry: 13 / 38 / 38 / 51 / 13 mm (1/2" / 1-1/2" / 1-1/2" / 2" / 1/2")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Impacts Per Minute (IPM)	High / Low: 0 - 39,000 / 0 - 9,000
No Load Speed (RPM)	High / Low: 0 - 2,200 / 0 - 600
Max Fastening Torque	Hard / Soft: 64 / 30 N-m (570 / 270 in.lbs.)
Max Lock Torque	65 N-m (580 in.lbs.)
Dimensions (L x W x H)	w/ BL4020 / BL4025: 174 x 86 x 265 mm (6-7/8 x 3-3/8 x 10-3/8") w/ BL4040: 174 x 86 x 272 mm (6-7/8 x 3-3/8 x 10-3/4") w/ BL4050F: 174 x 86 x 294 mm (6-7/8 x 3-3/8 x 11-5/8")
Net weight	2.0 - 2.6 kg (4.4 - 5.7 lbs.)

DF001G Cordless Driver Drill 40V max

40Vmax XGT BL AFT Cordless
13 mm (1/2") 125 N-m (1,100 in.lbs.)
Driver Drill



XGT BL AFT XPT



Capacity	Steel: 20 mm (13/16") Wood (Auger-Bit): 50 mm (2") Wood (Self-Feed Bit): 76 mm (3") Sliding Board: 220 mm (8-5/8")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High / Low: 0 - 2,600 / 0 - 650
Max Fastening Torque	Hard / Soft: 140 / 68 N-m (1,240 / 600 in.lbs.)
Max Lock Torque	125 N-m (1,100 in.lbs.)
Dimensions (L x W x H)	w/ BL4020 / BL4025: 181 x 86 x 275 mm (7-1/8 x 3-3/8 x 10-7/8") w/ BL4040: 181 x 86 x 282 mm (7-1/8 x 3-3/8 x 11-1/8")
Net weight	2.7 - 3.0 kg (5.9 - 6.6 lbs.)